

item number	A (mm)	B (mm)	thickness of metal sheet (mm)
NR 50X62_S	63	40	0,8
NR 50X125_S	126	40	0,8
NR 100X125_S	126	90	0,8
NR 100X250_S	251	90	0,8
NR 50X62_F	63	40	0,8
NR 50X125_F	126	40	0,8
NR 100X125_F	126	90	0,8
NR 100X250_F	251	90	0,8



product description: The reduction is used to change the width of cable trays running through MARS cable trays.
 To fix the connection use the bolt NSM 6X10. To protect the cables, the bolt head is inside the cable tray.
 A bolt with a GMT surface finish is used for a tray with an F surface finish.

surface finish: S - Pre-Galvanized, zinc-layer 15 - 27 µm
 F - Hot Dip Galvanized, zinc-layer 50 - 100 µm
 EC - epoxy paint for indoor use - total paint, 60 µm

sales amount: á 1 pc

meets the requirements: EN 61537:02

classification: ČSN 73 0895 P 90-R
 DIN 4102-12 E90
 STN 92 0205 PS 90

Fire classification is depend on the specific conditions of the cable tray, detailed in the catalog Systems with maintained functionality in fire.

Systems may be supplied with various surface finishes whereas the surface finish does not affect the determined maintained time of operability in fire.

storage: EN 60721-3-1

