



product description: intended for installation to the distribution of low voltage
 designed for installation in the corner between the floor and wall
 edge with softened spray application for better adhesion to the floor and/or wall
 suitable for use with floating floors
 accessories for instrument installation
 possibility to install in places with risk of flammable gases and vapor – danger zone 2
 possibility to install in places with explosive risk of dust – danger zone 22
 White trunkings are not a breeding ground for bacteria* , tested in SZÚ according to ČSN EN ISO 846:2019



material: PVC - Pb-free
 self-snuffing: yes, within 30 s
 temperature resistance: -5 - +60 °C
 flaming loop test: 850 °C
 impact strength: 2 J
 protection types: IP40
 fire class for underlying material: A1-F
 inside area: 350 mm²
 length tolerance: ±10 mm
 weight: 0,24 kg/m
 meets the requirements: EN 50085-1 ed.2:06, EN 50085-2-1:07
 storage: ČSN 64 0090



usage of inner trunking cross-section (60%):	orientation cable diameter (mm)	6	7	8	8,5	9	9,5	10	11	12
	number of inserted cables	5	3	3	2	1	1	1	1	1

chemical resistance: YES: amoniak 25%, distilled water, ethanol 50%, sodium hydroxide 60%, hydrofluoric acid 40%, acetic acid 5%, sulfuric acid 96%, medicinal oil, methanol, olive oil, petroleum, hydrogen peroxide 20%, transformer oil, sodium carbonate
 NO: aceton, benzen, chlorinated hydrocarbons, tetrachlorocarbon

accessories: instrument carrier PNLP 35 2Z...
 instrument carrier PNQ LP 35_HB

item number	length	color	package	package - description	note
LP 35_HD	2 m	white RAL 9003	20 m	carton	-
LP 35_I1	2 m	imitation - pink birch	20 m	carton	-
LP 35_I2	2 m	imitation - dark oak	20 m	carton	-
LP 35_SD	2 m	brown - light wood	20 m	carton	-
LP 35_TD	2 m	brown - dark wood	20 m	carton	-
8861 L_HB		white RAL 9003	10 / 1500 pcs	foil / carton	
8861 L_I1		imitation - pink birch	1 / 50 / 500 pcs	bag / bag / carton	end left
8861 L_I2		imitation - dark oak	1 / 50 / 500 pcs	bag / bag / carton	
8861 L_SD		brown - light wood	1 / 50 / 500 pcs	bag / bag / carton	
8861 P_HB		white RAL 9003	10 / 1500 pcs	foil / carton	
8861 P_I1		imitation - pink birch	1 / 50 / 500 pcs	bag / bag / carton	end right
8861 P_I2		imitation - dark oak	1 / 50 / 500 pcs	bag / bag / carton	
8861 P_SD		brown - light wood	1 / 50 / 500 pcs	bag / bag / carton	
8865_HB		white RAL 9003	10 / 800 pcs	foil / carton	
8865_I1		imitation - pink birch	1 / 50 / 400 pcs	bag / bag / carton	inner corner
8865_I2		imitation - dark oak	1 / 50 / 400 pcs	bag / bag / carton	
8865_SD		brown - light wood	1 / 50 / 400 pcs	bag / bag / carton	
8866_HB		white RAL 9003	10 / 640 pcs	foil / carton	
8866_I1		imitation - pink birch	1 / 50 / 250 pcs	bag / bag / carton	outer corner
8866_I2		imitation - dark oak	1 / 50 / 250 pcs	bag / bag / carton	
8866_SD		brown - light wood	1 / 50 / 250 pcs	bag / bag / carton	

the accessories and covers _I2 are suitable for _I2 and _TD trunkings

*List of bacteria that have been tested:

ESCHERICHIA COLI, STAPHYLOCOCCUS AUREUS, KLEBSIEL/A PNEUMONIAE, PSEUDOMONAS AERUGINOSA, ENTEROCOCCUS FAECALIS, BACILLUS SUBTILIS, SALMONELLA ENTERICA, LEGIONELLA PNEUMOPHILA, CANDIDA ALBICANS