

type number: **NP 30X15X1.20_S**
NP 30X15X1.20_ZM

thickness of metal sheet: 1,2 mm

product description: The load bearing profile is designed for supporting a cable route on threaded rods or for cable route formed by PKC cable clamps.

Load bearing profile + threaded rods:
 The load bearing profile is fixed by using two threaded rods ZT 8 + nuts M 8 + washers PD 8.

NSM 6X10 bolts are used to attach the cable tray to the load bearing profile.
 The load bearing profile is recommended for a route width of max. 300 mm.
 Max. load for one mounting point is 100 kg

Load bearing profile + PKC clamps:
 PKC clamps are used for cable fastening.
 The load bearing profile is fixed by using anchor KPO 6 or bolt SB 6.3X35.
 Possibility to use vertical cable routes.

ZM surface finish load bearing profile shall be used for ZM or F surface finish trays.

surface finish: S - Pre-Galvanized steel according to ČSN EN 10346, ČSN EN 10143, zinc-layer 15-27 µm

ZM - Pre-Galvanized steel with admixture of magnesium and aluminum according to ČSN EN 10346, ČSN EN 10143, protective layer 18-31 µm (replacement of hot dip galvanizing)

sales amount: 2 m

meets the requirements: ČSN EN 61537:02

classification : ČSN 73 0895 P 90-R
 DIN 4102-12 E 90
 STN 92 0205 PS 90
 Fire classification is depend on the specific conditions of the cable tray, detailed in the catalog Systems with maintained functionality in fire.
 Product approved for standard and non-standard constructions.

storage: ČSN EN 61537:02

